



PSF SYNTH

Product Description:

PSF SYNTH is a fully synthetic power steering fluid dedicated for most common passenger cars and light-duty commercial vehicles.

PSF SYNTH is formulated from specially selected high quality fully synthetic Poly-alpha olefin (PAO) base stocks in combination with a special detergent additive to achieve the following performance:

- Excellent cleaning properties
- Improves performance and smoothness of operation in power steering systems
- High Viscosity Index
- Miscible with all common power steering fluids.
- Very bright and light colored oil helps improves visual detection when flushing is completed; reducing total volume of used flushing oil



PSF SYNTH is recommended where the following OEM specifications / part numbers are required:

Acura/Honda PN 08206-9002	Bentley JNV862564F	American Motors Corporation C4124	Chrysler MS-11655B
Audi PN G002000	DaimlerChrysler MS5931F&G	BMW ZF TE-ML 09	DaimlerChrysler MS9602
DaimlerChrysler MS1872	DaimlerChrysler MS1872	Fendt X 902 011 622	Ford M2C195A
DaimlerChrysler MS9933A	Ford ESW-M2C128 C&D	Ford M2C128D	Ford MS2195A
Ford M2C33F	Ford M2C138CJ	Ford WSS M2C204A	GM 9985010
Ford M2C138C	GM 89021184	Hyundai/Kia PSF-3	Hyundai 00232-19017
GM 9985835	Land Rover LR003401	MAN M3289	Massey Ferguson
Iveco 18-1823	Mitsubishi PS Fluid/Diamond	SP III	Navistar TMS 6810
MB 345.0	Nissan PSF-II	Opel B 040 0070	Opel B 040 2012
NH 610A	Porsche 000 043 203 33	PSA B71 2710	PSA S71 2710
Porsche 000 043 206 56	Saab 3032 380	Saab PSF 2634	Saab PSF 45 30 09 800
Saab 93160548	Saab PN 30 09 800	SDFG OF1611S	Subaru PN K0209A0080
Saab PSF 93160548	Volvo 1161529	Volkswagen VW-TL-52 146.01	
Volkswagen VW-TL-570-26		Volvo 30741424	
VW G 004 012			

PSF SYNTH is suitable for use where these specifications are required for power steering fluid. It is not suitable in other applications such as automatic transmissions.

Property	Unit	Test Method	Typical Value
Color			Green
Density@15°C	kg/m ³	ASTM D4052	829
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	21.4
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.8
Viscosity Index		ASTM D2270	315
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-63

Product Nr: 43190
Date Superseded: 26-01-2021

Date Issued: 09-08-2022
Revision nr: 05