



# MOTOR OIL VX 5W-30

## Product Description:

**MOTOR OIL VX 5W-30** is a high performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed and also suitable for vehicles where MB 229.51 and BMW LL-04 are required. Also suitable for use for vehicles where originally VW 506.01 is required.

**MOTOR OIL VX 5W-30** is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersions and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

**MOTOR OIL VX 5W-30** meets the following performance criteria:

Approved	VW 504.00 / 507.00	MB-approval 229.52
Meets	ACEA C3 Porsche C30 MB 229.51	API SN BMW LL-04



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	851
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	66
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	11.6
Viscosity Index		ASTM D2270	173
Viscosity CCS @-30°C, max	cP	ASTM D5293	5534
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45
Total Base Number	mgKOH/g	ASTM D2896	8.8
Sulphated Ash	%Wt	ASTM D874	0.7

Product Nr: 42240  
Date Superseded: 18-01-2021

Date Issued: 3-10-2024  
Revision nr: 10