



MOTOR OIL XT 5W-30

Product Description:

MOTOR OIL XT 5W-30 is a high performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed. **MOTOR OIL XT 5W-30** is suitable for vehicles where MB 229.51 and BMW LL-04 are required.

Remark: not suitable for R5- and V10 TDI engines and engines where VAG norm VW 506.01 is being advised.

For vehicles within warranty or extended warranty we advise to use MOTOR OIL VX 0W-30 or MOTOR OIL VX 5W-30



MOTOR OIL XT 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

MOTOR OIL XT 5W-30 meets the following performance criteria:

ACEA C3 **VW 504.00 / 507.00** **MB 229.51**
BMW LL-04 > until 2019 **API SN**

| Property | Unit | Test Method | Typical Value |
|---------------------------|--------------------|-------------|---------------|
| SAE Grade | | SAE J300 | 5W-30 |
| Density@ 15°C | kg/m ³ | ASTM D4052 | 851 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 68.5 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 11.7 |
| Viscosity Index | | ASTM D2270 | 167 |
| Viscosity CCS @-30°C, max | cP | ASTM D5293 | 4900 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -37 |
| Total Base Number | mgKOH/g | ASTM D2896 | 9.3 |
| Sulphated Ash | %Wt | ASTM D874 | 0.79 |

Product Nr: 42310
Date Superseded: 09-03-2023

Date Issued: 15-11-2024
Revision nr: 07