



MOTOR OIL CT 5W-30

Product Description:

MOTOR OIL CT 5W-30 is a cost effective fuel saving MID SAPS technology and used in light duty vehicles fitted with direct injection, turbocharges and after-treatment systems, gasoline catalytic converter, or diesel particulate filter technology.

MOTOR OIL CT 5W-30 is based on high performance base oils in combination with a specially selected additive technology to ensure the following properties:

- Strong Fuel Economy Performance
- Excellent Engine Durability
- Excellent Engine Compatibility
- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Good low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.



MOTOR OIL CT 5W-30 meets the following performance criteria:

API SP **ACEA C2** **MB 229.31** **MB 229.51**
API SN/CF **ACEA C3** <- 2019 BMW LL-01 applications
Dexos 2

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	849
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.8
Viscosity Index		ASTM D2270	169
Viscosity CCS @-30°C	cP	ASTM D5293	5600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.1
Sulphated Ash	%Wt	ASTM D874	0.79

Product Nr: 42315
Date Superseded: 22-3-2022

Date Issued: 3-9-2024
Revision nr: 03