

MOTOR OIL SYNTHETIC OW-16

Product Description:

MOTOR OIL SYNTHETIC 0W-16 is the advanced synthetic energy conserving motor oil specially developed for the most modern high output gasoline and turbocharged engines in (Hybrid)passenger cars, sport utility vehicles and light-duty trucks, operating on ethanol-containing fuels up to E85. It is formulated to help improve & retain fuel economy and protect vehicle emission system & turbocharger components.

MOTOR OIL SYNTHETIC 0W-16 is based on exceptional quality synthetic base oil in combination with a special selected additive package to reach to following properties:

- Improved protection against stochastic pre-ignition
- Improving sludge protection, piston cleanliness, turbo-charger protection, seal compatibility, wear protection
- Special friction modifiers used in this Energy conserving oil help improving & retaining fuel economy.
- Offers excellent lubrication at low temperatures and protect engine at high temperatures.
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution (VOCs).
- Advanced additive chemistry helps in emission system durability.
- Compatible with ethanol-containing fuels up to E85.

MOTOR OIL SYNTHETIC 0W-16 meets the following performance criteria:

API SP	API SN	APLSN + RC	II SAC GF-6B

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-16
Density@15°C	kg/m³	ASTM D4052	846
Kin. Viscosity @40°C	mm²/s	ASTM D7042	39.3
Kin. Viscosity @100°C	mm²/s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	161
Viscosity CCS @-35°C, max	сР	ASTM D5293	4800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.2

Product Nr: 42160 Date Issued: 23-08-2022

Date Superseded: 23-02-2021 Revision nr: 01

