



MOTOR OIL SF

15W-40

Product Description:

MOTOR OIL SF 15W-40 is a multi functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger car and light vans with or without turbo compressor. MOTOR OIL SF 15W-40 is not suited for engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SF 15W-40 is formulated with special selected base stocks in combination with unique additive package to reach the following properties:

- Stable viscosity index.
- Good protection against rust, corrosion and wear.
- Good dispersancy and detergency properties.
- Good antifoam properties.

MOTOR OIL SF 15W-40 exceeds the following performance criteria:

API SF/CD

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m ³	ASTM D4052	865.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	93.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.6
Viscosity Index		ASTM D2270	146
Viscosity CCS @-20°C, max	cP	ASTM D5293	3780
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	%Wt	ASTM D874	0.66

Product Nr: 42120

Date Superseded: 18-01-2021

Date Issued: 27-11-2024

Revision nr: 05

