



ENGINE OIL HDX

25W-60

Product Description:

ENGINE OIL HDX 25W-60 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

ENGINE OIL HDX 25W-60 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

ENGINE OIL HDX 25W-60 exceeds the following performance criteria:

API CI-4	API SL	ACEA E7	JASO DH-1
MAN M 3275	Volvo VDS-3	Deutz DQC-III	MTU Type 2
Mack EO-N	Cummins CES 20077/20078	Caterpillar ECF-1a	Renault RLD-2
DDC 93K215	DTFR 15B110 (MB 228.3)	Caterpillar ECF-2	Global DHD-1



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	25W-60
Density@15°C	kg/m ³	ASTM D4052	895
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	241.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	23.7
Viscosity Index		ASTM D2270	122
Viscosity CCS @-10°C, max	cP	ASTM D2270	7800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
Total Base Number	mgKOH/g	ASTM D2896	11.5
Sulphated Ash	%Wt	ASTM D874	1.5

Product Nr: 42450
Date Superseded: 26-01-2021

Date Issued: 6-12-2024
Revision nr: 05