



SUPER TRACTOR OIL

15W-40

Product Description:

SUPER TRACTOR OIL 15W-40 is a high quality so called “Super Tractor Oil Universal” (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed “wet brakes”. This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).



SUPER TRACTOR OIL 15W-40 is formulated on mineral base stocks in combination with an unique additive package to reach the following properties;

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

SUPER TRACTOR OIL 15W-40 exceeds the following performance criteria:

Engine Spec	API CG-4/CF-4/CE/SF	MB 227.1	ACEA E3
UTTO/STOU Spec	JD J20C/D	Ford M2C86B/C	Ford M2C 134-A/C/D
	Ford M2C159B/C	FNH 82009201	Allison C-4
	Case MS 1204/6/7/9	MF M 1135/1139	MF M 1143/1145
	Cat TO-2	API GL-4	MF 1127-A
	FNH-2-C-201.00	NH 410-B	NH 420-A
	ZF TE-ML 05K, 06B/C, 07B/D		
Hydr. Spec	Eaton M-2950S	Eaton I-280-S	Danfoss

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m ³	ASTM D4052	883.1
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	96.6
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	140
Viscosity CCS @-20°C, max	cP	ASTM D5293	5800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	10.5

Product Nr: 43290
Date Superseded: 12-12-2019

Date Issued: 3-1-2025
Revision nr: 04