



MOTOR OIL VLV 0W-30

Product Description:

MOTOR OIL VLV 0W-30 is a fuel saving oil based on 100% synthetic technology specially designed for use in Volvo 5 cylinder Petrol and 6 Cylinder Petrol engines with or without turbocharger where Volvo VCC 95200377 is required.

MOTOR OIL VLV 0W-30 can also be used for applications where an oil according to ACEA A5/B5 or API SL is recommended by the manufacturer.

MOTOR OIL VLV 0W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Protection to wear by cold start.
- Very good low temperature properties.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Added fuel economy

MOTOR OIL VLV 0W-30 exceeds the following performance criteria:

Approved: Volvo VCC 95200377

Exceeds: API SL ACEA A5/B5



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density@15°C	kg/m ³	ASTM D4052	844
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	52.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10
Viscosity Index		ASTM D2270	180
Viscosity CCS @-35°C, max.	cP	ASTM D5293	5100
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	10.1
Sulphated Ash	%Wt	ASTM D874	1.00

Product Nr: 45410
Date Superseded: 4-5-2021

Date Issued: 29-11-2024
Revision nr: 02